

# **PowerWalker Inverter 2000**

Inverter / Charger System

2000VA Inverter

Schuko outlet, Rack/Tower design

Built-in 10A super charger

Off mode charging / High Frequency design

3-steps intelligent charging control to reduce recharging time



Item-No. 10120208



Schuko Outlets

#### **Product Features**

The Inverter/Charger system converts DC power to AC power with amazing transfer efficiency. Appliances such TVs, stereos, notebook computers can be connected for the uninterruptible power. When encountering utility power failure, this series will transfer from "LINE mode" to "Inverter mode" for acquiring the power from battery supply. With the continuous output and compact design, this series is perfect for any home or SMB (small medium business) environment.

- User selectable for accepting wider input voltage range
- Full automatic and silent operation
- Rack/Tower design
- Built-in 10A super charger
- 3-steps intelligent charging control to reduce recharging time
- High Frequency Design
- Off mode charging
- Compact size for convenient use and storage



2-in1 Rack/Tower design



LED Display, On/Off button





### **Technical Details**


### **Product Features**

	•
Capacity	2000VA / 1200W
Input	
Voltage	220/230/240VAC
Voltage Range	170-280VAC (Narrow Range)
	90-280VAC (Wide Range)
Output	
Voltage	230VAC
Voltage Regulation (Battery Mode)	+10 % / -18%
Frequency	50 or 60Hz
Freq. Regulation (Battery Mode)	± 0.5 Hz
Waveform	Modified Sine Wave
Transfer Time	
Typical	20ms
Max.	40ms
Charger	
	Three stage profile (CC/CV/Floating)
Charger algorithm	CC=Constant Current CV=Constant Voltage
Charger current	10A ± 1A
DC Voltage	24V
Overcharge	
Protection	30V ± 0.8V
Battery	
Туре	24V
Recharge Time	Depends on connected battery
Optional	Inverter is supplied without battery
LED Display Indicators	
AC Mode	Green lightning
Battery Mode	Yellow lightning
Bat. Charging Mode	Green flashing every 2 second
Overload	Red flashing every 0.5 second
Fault	Red lightning
Audio Indicators	
Low Battery	Beep every 2 seconds
Overload	Beep every 0.5 second
Fault	Continuous Beep
Full Protection	
Discharge	Yes
Overcharge	Yes
Overload	Yes
Short circuit	Yes

### **Connections**

Outlets	Schuko
Product Details	
Dimensions	224 x 255 x 80 mm
Colour	Black
Weight	2.5 kg
Fan Control	Auto OFF: in LINE mode (if charge current below 3A (±1A) ON: in battery mode and line mode if charge current above 3A (±1A)
Noise Level	< 50dB
Model Code	Inverter 2000
Environment	
Temperature	0°C – 40°C
Humidity	0 – 90 % RH (non-condensing)
Package Content	
Package Content	PowerWalker Inverter 2000, DC cable, Input Power cable, manual
Logistic Data	
Giftbox Language	EN
Manual Language	EN/DE/FR
Dimension/Giftbox	322 x 123 x 266 mm
Weight/Giftbox	3.04
Pieces/Carton	9
Pieces/Palette	189
Item Number	10120208
EAN	4260074975956
Warranty	24 Month

### **Typical Installation**



Version: EN 03/09/2013

We reserve the right for technical changes and mistakes





### **Application Examples**

#### **Home Entertainment**

74cm TV Cassette/CD/Radio - Portable Radio Etc.



### **Home Appliances**

FAN Etc.



### **Office Equipments**

Notebook Modem/Router Etc.



### Lightning

Lights - Energy Saver **Lights - Standard Bulbs Lights - Fluorescent Tube** 



## **Optional Input Power Source can be** Generator, Photovoltaic, Wind, Hydro

